

Product data sheet

XS8D1A1NAL2

Inductive sensor, XS8, 80x80x26 mm, PBT, Sn 60 mm, NPN, NO, cable 2 m, form D flat, 12...24 VDC

Main

Range of product	Telemecanique Inductive proximity sensors XS
Series name	General purpose
Sensor name	XS8
Sensor type	Inductive proximity sensor
Sensor design	Flat form 80 x 80 x 26
Device application	Not applicable
ETIM classification	ETIM 9 - EC002714 - Inductive proximity switch
Body type	Fixed
Material	Plastic
Front material	PBT
Enclosure material	PBT
[Sn] nominal sensing distance	40 mm flush mountable, 60 mm non flush mountable
Wiring technique	3-wire
Detector flush mounting acceptance	Non flush mountable
Delay response	0.3 ms
Product certifications	CSA Ecolab UL
Marking	CE
Indivisible sale quantity	1

Complementary

Sensing range	> 40...60 mm
Electrical connection	Cable
Cable length	2 m
Cable composition	3 x 0.34 mm²
Wire insulation material	PVC
Supply voltage limits	10-36 V DC
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Switching capacity in mA	<= 200 mA DC with overload and short-circuit protection

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Voltage drop	<2 V (closed)
Current consumption	<= 10 mA no-load
Output circuit type	DC
Type of output signal	Discrete
Detection face	Frontal
Discrete output type	NPN
Discrete output function	1 NO
Switching frequency	<= 150 Hz
Differential travel	1...15 % of Sr
Fine adjustment zone	20-40 mm flush mountable, 20-60 mm non flush mountable
Delay first up	10 ms
Delay recovery	6 ms
Residual current	1.5 mA open state
Height	80 mm
Width	80 mm
Depth	26 mm
Size	26 mm
Product weight	0.39 kg

Environment

IP degree of protection	IP68 double insulation conforming to IEC 60529
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C
Shock resistance	50 gn for 11 ms conforming to IEC 60068-2-27
Vibration resistance	25 gn amplitude = +/- 2 mm (f = 10-55 Hz) conforming to IEC 60068-2-6

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Warranty

Warranty	18 months


Packing Units

Country of origin	FR (France)
Unit type of package 1	PCE
Number of units in package 1	1
New Package 1 GTIN-13	3666916009758

Package 1 height	6.7 cm
Package 1 width	9.6 cm
Package 1 length	13.2 cm
Package 1 weight	0.39 kg
Unit type of package 2	S01
Number of units in package 2	5
New Package 2 GTIN 14	13666916009755
Package 2 height	15 cm
Package 2 width	15 cm
Package 2 length	40 cm
Package 2 weight	6.36 kg
Unit type of package 3	S02
Number of units in package 3	14
New Package 3 GTIN 14	23666916009752
Package 3 height	15 cm
Package 3 width	30 cm
Package 3 length	40 cm
Package 3 weight	6.36 kg

Technical Drawings


Dimensions




(1)
(2)
(3)

Setting-up


Minimum Mounting Distances (mm)



Minimum Mounting Distances (mm)




Minimum Mounting Distances (mm)



Side by Side
Face to Face
Facing a Metal Object

Wiring Schemes

NPN



BU :
BN :
BK :