

Product data sheet

XUB0BPSNM12

Photoelectric sensor XUB, metal, multimode, 12...24 VDC, M12, NO/NC

Main

Range of product	Telemecanique Photoelectric sensors XU
Series name	General purpose multimode
Sensor name	XUB
Electronic sensor type	Photo-electric sensor
Sensor design	Cylindrical M18
Product specific application	Not applicable
ETIM classification	ETIM 9 - EC002716 - Through beam photoelectric sensor
Material	Metal
Lens material	PMMA
Enclosure material	Nickel plated brass
[Sn] nominal sensing distance	3-3 m polarised reflex need reflector XUZC50, 20-20 m thru beam need a transmitter XUB0BKSNM12T, 0.12-0.12 m diffuse with background suppression, 0.3-0.3 m diffuse
Maximum sensing distance	0.12 m diffuse with background suppression, 0.4 m diffuse, 30 m thru beam, 4.5 m polarised reflex
Wiring technique	3-wire
Diameter	18 mm
Detection system	Multimode
Line of sight type	Axial
Delay response	2 ms
Indivisible sale quantity	1

Complementary

Sensing range	> 0...20 m
Electrical connection	1 male connector M12, 4 pins
Supply voltage limits	10-36 V DC
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Supply circuit type	DC
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)
Maximum voltage drop	<1.5 V (closed state)
Current consumption	35 mA no-load

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Emission	Infrared diffuse, infrared diffuse with background suppression, infrared thru beam, red polarised reflex
Setting-up	Self teaching
Output type	Solid state
Type of output signal	Discrete
Add on output	Without
Discrete output type	PNP
Discrete output function	1 NO or 1 NC programmable
Switching frequency	250 Hz
Status LED	1 LED (green) for supply, 1 LED (red) for instability, 1 LED (yellow) for output state
Delay first up	200 ms
Delay recovery	2 ms
Length	78 mm
Product weight	0.055 kg

Environment

IP degree of protection	IP65 double insulation conforming to IEC 60529, IP67 double insulation conforming to IEC 60529, IP69K double insulation conforming to DIN 40050
Ambient air temperature for storage	-40...70 °C
Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60068-2-27
Vibration resistance	7 gn, amplitude = +/- 1.5 mm (f = 10-55 Hz) conforming to IEC 60068-2-6

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Warranty

Warranty	18 months

Packing Units

Country of origin	ID (Indonesia)
Unit type of package 1	PCE
Number of units in package 1	1
New Package 1 GTIN-13	3666916033630
Package 1 height	4.2 cm
Package 1 width	6.7 cm
Package 1 length	9.6 cm
Package 1 weight	0.055 kg
Unit type of package 2	S01
Number of units in package 2	22

New Package 2 GTIN 14	13666916033637
Package 2 height	15 cm
Package 2 width	15 cm
Package 2 length	40 cm
Package 2 weight	1.765 kg
Unit type of package 3	CAR
Number of units in package 3	1
New Package 3 GTIN 14	23666916033634
Package 3 height	6.5 cm
Package 3 width	9.5 cm
Package 3 length	4.1 cm
Package 3 weight	0.07 kg

Technical Drawings

Dimensions



Wiring Schemes

M12 Connector



- 1 : (+)
- 2 : Beam break input (1)
- 3 : (-)
- 4 : OUT/Output
- (1) Beam break input on thru-beam transmitter only

Wiring Schemes

Receiver, PNP Output



- 1 : (+)
- 2 : Beam break input (1)
- 3 : (-)
- 4 : OUT/Output
- (1) Beam break input on thru-beam transmitter only
- BN : Brown
- BU : Blue
- BK : Black

Detection Curves

With Thru-beam Accessory (Thru-beam)



Detection Curves

Without Accessory (Diffuse)



- 1 : White 90%
- 2 : Grey 18%

Object 10 x 10 cm

Detection Curves

Without Accessory (Diffuse with background suppression)



- 1 : White 90%
- 2 : Grey 18%
- 1 : White 90%
- 2 : Grey 18%

Object 10 x 10 cm

Detection Curves

With reflector (Polarised reflex)



- 1 : White 90%
- 2 : Grey 18%
- 1 : White 90%
- 2 : Grey 18%

With reflector XUZC50

Detection Curves

Variation of Usable Sensing Distance Su (Without accessory, with adjustable background suppression)



- 1 : White 90%
- 2 : Grey 18%
- 1 : White 90%
- 2 : Grey 18%

Variation of Usable Sensing Distance Su (Without accessory, with adjustable background suppression)



- 1 : White 90%
- 2 : Grey 18%
- 1 : White 90%
- 2 : Grey 18%
- A-B : Object reflection coefficient
- (1) Black 6%
- (2) Grey 18%
- (3) White 90%
- (4) Sensing range
- (5) Non sensing zone (matt surfaces)

Detection Curves

Variation of Usable Sensing Distance



- 1 : White 90%
- 2 : Grey 18%
- 1 : White 90%
- 2 : Grey 18%
- A-B : Object reflection coefficient
- (1) Black 6%
- (2) Grey 18%
- (3) White 90%
- (4) Sensing range
- (5) Non sensing zone (matt surfaces)

Variation of Usable Sensing Distance



- 1 : White 90%
- 2 : Grey 18%
- 1 : White 90%
- 2 : Grey 18%
- A-B : Object reflection coefficient
- (1) Black 6%
- (2) Grey 18%
- (3) White 90%
- (4) Sensing range
- (5) Non sensing zone (matt surfaces)
- A-B : Object reflection coefficient
- (1) Black 6%
- (2) Grey 18%
- (3) White 90%
- (4) Sensing range
- (5) Non sensing zone (matt surfaces)