

Product data sheet

XUK0ARCTL2T

Photoelectric emitter XUK, thru-beam, Sn 30 m, 24...240 VAC, cable 2 m

Main

Range of product	Telemecanique Photoelectric sensors XU
Series name	General purpose multimode
Sensor name	XUK
Electronic sensor type	Photo-electric sensor transmitter
Sensor design	Compact 50 x 50
Product specific application	Not applicable
ETIM classification	ETIM 9 - EC002716 - Through beam photoelectric sensor
Material	Plastic
Lens material	PMMA
Enclosure material	PBT
[Sn] nominal sensing distance	30-30 m thru beam need a receiver
Maximum sensing distance	35 m thru beam
Wiring technique	2-wire
Detection system	Thru beam
Indivisible sale quantity	1

Complementary

Sensing range	> 15...30 m
Electrical connection	Cable
Cable length	2 m
Supply voltage limits	10-264 V DC, 20-264 V AC
[Us] rated supply voltage	12...240 V DC, 24...240 V AC
Supply circuit type	AC/DC
Switching capacity in mA	3 A (cos φ = 1 for 0.5 million cycles at 1 operating cycle per second at 250 V)
Maximum voltage drop	<1.5 V (closed state)
Emission	Infrared thru beam
Setting-up	Without sensitivity adjustment
Time delay range	0...10 s monostable, on-delay or off-delay (programmable) delay
Switching frequency	20 Hz

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Status LED	1 LED (green) for supply on
Height	50 mm
Width	18 mm
Depth	50 mm

Environment

IP degree of protection	IP65 double insulation conforming to IEC 60529
Ambient air temperature for storage	-40…70 °C
Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60068-2-27
Vibration resistance	7 gn, amplitude = +/- 1.5 mm (f = 10-55 Hz) conforming to IEC 60068-2-6

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Warranty

Warranty	18 months


Packing Units

Country of origin	ID (Indonesia)
Unit type of package 1	PCE
Number of units in package 1	1
New Package 1 GTIN-13	3666916033463
Package 1 height	13.2 cm
Package 1 width	9.5 cm
Package 1 length	4.2 cm
Package 1 weight	0.14 kg
Unit type of package 2	S02
Number of units in package 2	22
New Package 2 GTIN 14	13666916033460
Package 2 height	30 cm
Package 2 width	15 cm
Package 2 length	40 cm
Package 2 weight	3.8985 kg
Unit type of package 3	CAR
Number of units in package 3	1
New Package 3 GTIN 14	23666916033467
Package 3 height	13.2 cm
Package 3 width	9.5 cm

Package 3 length	4.2 cm
Package 3 weight	0.154 kg


Technical Drawings

Dimensions



Wiring Schemes

Thru-beam Transmitter AC



- BN : Brown
- BU : Blue

Detection Curves

With Thru-beam Accessory (Thru-beam)

