

Product data sheet

XUK2LAPSMM12R

Photoelectric receiver XUK, photo electric laser sensor, XUK, thru-beam receiver, Sn 30 m, 10...30 VDC, M12, PNP, NO/NC

Main

Range of product	Telemecanique Photoelectric sensors XU
Series name	Application assembly Application material handling
Sensor name	XUK
Electronic sensor type	Photo-electric sensor
Sensor design	Compact 50 x 50
Product specific application	Not applicable
ETIM classification	ETIM 9 - EC002716 - Through beam photoelectric sensor
Material	Plastic
Lens material	PMMA
Enclosure material	ABS/PC
[Sn] nominal sensing distance	25-25 m thru beam need transmitter XUK2LAKSMM12T
Maximum sensing distance	30 m thru beam
Wiring technique	4-wire
Detection system	Thru beam
Delay response	0.14 ms
Indivisible sale quantity	1

Complementary

Sensing range	> 15...30 m
Electrical connection	1 male connector M12, 4 pins
Supply voltage limits	10-30 V DC
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Supply circuit type	DC
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)
Maximum voltage drop	<2.4 V (closed state)
Current consumption	<= 30 mA no-load
Emission	Red thru beam
Setting-up	Using teach button or remote teaching
Output type	Solid state

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Type of output signal	Discrete
Add on output	Without
Discrete output type	PNP
Discrete output function	1 NO or 1 NC programmable
Status LED	1 LED (green) for supply on, 1 LED (yellow) for output state, 1 LED (red) for alignment assistance
Delay first up	300 ms
Delay recovery	0.14 ms
Height	50 mm
Width	23 mm
Depth	50 mm
Product weight	0.035 kg

Environment

IP degree of protection	IP67 conforming to IEC 60529, IP69K conforming to DIN 40050
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for operation	-20-60 °C, -20-50 °C, UL certified
Ambient air temperature for storage	-20...80 °C
Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60947-5-2
Vibration resistance	7 gn, amplitude = +/- 1.5 mm (f = 10-55 Hz) conforming to IEC 60068-2-6

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Warranty

Warranty	18 months


Packing Units

Country of origin	DE (Germany)
Unit type of package 1	PCE
Number of units in package 1	1
New Package 1 GTIN-13	3666916037638
Package 1 height	3 cm
Package 1 width	6 cm
Package 1 length	10 cm
Package 1 weight	0.032 kg
Unit type of package 2	S01
Number of units in package 2	28

New Package 2 GTIN 14	13666916037635
Package 2 height	15 cm
Package 2 width	15 cm
Package 2 length	40 cm
Package 2 weight	1.544 kg
Unit type of package 3	CAR
Number of units in package 3	1
New Package 3 GTIN 14	23666916037632
Package 3 height	10 cm
Package 3 width	3 cm
Package 3 length	6 cm
Package 3 weight	0.032 kg


Technical Drawings

Dimensions



- (1) Receiver optical axis
- (2) Transmitter optical axis


Wiring Schemes Using M12 Connector



- 1 : (+)
- 2 : ET/Lock (1)
- 3 : (-)
- 4 : Output
- BN : Brown
- WH : White
- BU : Blue
- BK : Black
- +UB : External teach
- -UB : Pushbutton locking
- (1) ET/Lock. ET: External Teach, Lock: Pushbutton locking

Curves


Excess Gain Curve



- (X) Distance (m)
- (Y) Gain

Curves

Size of Luminous Point



- (X) Distance (m)
- (Y) Gain
- (X) Distance (m)
- (Y) Size (mm)