

Product data sheet

XUK8TAKDMM12

Photoelectric sensor XUK, diffuse, Sn 5 m, 1 output IO-Link or auto PNP/NPN, ToF, 2Q

Main

Range of product	Telemecanique Photoelectric sensors XU
Series name	Application assembly Application material handling
Sensor name	XUK
Electronic sensor type	Photo-electric sensor
Sensor design	Compact 50 x 50
Product specific application	Distance measurement on object suppression of a background
ETIM classification	ETIM 9 - EC002719 - Light scanner with background masking
Material	Plastic
Lens material	PMMA
Enclosure material	ABS/PC
[Sn] nominal sensing distance	5-5 m diffuse with background suppression
Maximum sensing distance	5 m diffuse with background suppression
Wiring technique	5-wire
Detection system	Diffuse with background suppression
Delay response	2 ms
Product certifications	CE cULus Ecolab
Indivisible sale quantity	1

Complementary

Sensing range	> 0...5 m
Electrical connection	1 male connector M12, 5 pins
Supply voltage limits	18-30 V DC
[Us] rated supply voltage	24 V DC with reverse polarity protection
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)
Maximum voltage drop	<1.5 V (closed state)
Current consumption	<= 60 mA no-load
Emission	Red laser diffuse with background suppression class 1 conforming to IEC 60825-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Setting-up	Using teach button or remote teaching
Output type	Solid state
Type of output signal	Discrete
Discrete output type	IOLINK PNP or NPN
Discrete output function	1 NO or 1 NC programmable
Switching frequency	500 Hz
Status LED	1 LED (yellow) for output state, 1 LED (green/yellow) for supply on/output state
Delay first up	300 ms
Delay recovery	2 ms
Height	50 mm
Width	23 mm
Depth	50 mm
Product weight	0.035 kg

Environment

IP degree of protection	IP67 conforming to IEC 60529, IP69K conforming to IEC 60529, IP69K conforming to DIN 40050
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for operation	-20-50 °C, UL certified, -40-60 °C
Ambient air temperature for storage	-40...80 °C
Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60068-2-27
Vibration resistance	7 gn, amplitude = +/- 1.5 mm (f = 10-55 Hz) conforming to IEC 60068-2-6

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Warranty

Warranty	18 months

Packing Units

Country of origin	DE (Germany)
Unit type of package 1	PCE
Number of units in package 1	1
New Package 1 GTIN-13	3666916037461
Package 1 height	3 cm
Package 1 width	6 cm
Package 1 length	9.2 cm

Package 1 weight	0.055 kg
Unit type of package 2	S01
Number of units in package 2	28
New Package 2 GTIN 14	13666916037468
Package 2 height	15 cm
Package 2 width	15 cm
Package 2 length	40 cm
Package 2 weight	1.772 kg
Unit type of package 3	S02
Number of units in package 3	30
New Package 3 GTIN 14	23666916037465
Package 3 height	15 cm
Package 3 width	30 cm
Package 3 length	40 cm